



ESCHBACH SPECIAL-500 GRIZZLY

Class 2



Robust Fire fighting hose

High quality lay flat hose for all fire-fighting operations. With an additional synthetic PU-coating outside for increased abrasion resistance. Circular woven jacket out of 100% high tenacity synthetic yarn, with an inner liner made out of a vulcanized high quality EPDM-compound.

ADVANTAGES

- Lightweight lay flat hose
- Low friction loss
- High aging resistance
- Coating for improved resistance to oil, chemicals and dirt
- Cold-resistant up to -40°C
- Heat-resistant up to +100°C
- Easy maintenance and handling

APPROVALS

- DIN 14811 Class 2
- ÖNORM F 2106
- BS 6391 Type II
- Russian Maritime Register

SERVICE

- Standard colour red, other colours on request
- Relief version for better abrasion-resistance
- Individual marking available
- Binding with international couplings available on request
- Other diameters on request
- Available in lengths up to 1000 m depending on diameter

Diameter Inch (mm)	Weight g/m	Burst pressure	Working pressure	Test pressure
1" (25)	135	60	16	24
1.¼" (32)	175	60	16	24
1.½" (38)	205	60	16	24
1.⅔" (42)	240	60	16	24
1.¾" (45)	260	60	16	24
2" (52)	280	60	16	24
2.½" (65)	355	60	16	24
2.¾" (70)	385	60	16	24
3" (75)	470	60	16	24
4.⅓" (110)	745	35	12	18

Remark maximum working pressure:

The mentioned data is valid for the hose only. In case of fitted couplings the working pressure depends on the respective defined nominal pressure of the used coupling and the method of fitting.